



Mobilus XL

Technical data

-

capacity: 100 l

-

diameter: 400 mm

-

height: 930 mm

-

weight: 33 kg



Pump achievement

-

achievement* approx. 10 l / min.

-

Working pressure 2 bar

-

Aerial consumption approx. 2 m³ / h

Chassis

-

Width: 500 mm

-

Depth: 720 mm

-

Height: 1320 mm

-

Weight: 50 kg

*depends from the viscosity, tube, special cross section and the suction height

Mobilus L

Technical data

-

capacity: 100 l

-

diameter: 450 mm

-

height: 800 mm



Pump achievement

-

achievement* approx. 10 l / min.

-

Working pressure 2 cash

-

Air consumption approx. 2 m³ / h

Chassis

-

Width: 610 mm

-

Depth: 730 mm

-

Height: 1300 mm

Starterkit

6 mobile suction apparatuses 75 l, for the following media:



-

Petrol - medium AI - 100 litres = Mobilus L

-

Diesel - medium AIII - 75 litres with glass

-

Waste oil - medium AIII - 75 litres with rallying funnel

-

Brake fluid - medium B - 75 litres

-

Coolant - medium B - 75 litres

-

Screen water - medium B - 75 litres

Specifications:

-

Dimensions LBH (mm): 600 x 580 x in 1360

-

Height area rallying funnel: 1180 mm to 1800 mm

-

Diameter rallying funnel: 420 mm

-

Contents rallying funnel: 18 l

-

2 air pressure connections for Rectus coupling type 26

-

Recommended air pressure: 6

-

Suction volumes per vacuum build-up: From 45 to 50 l

-

Time per vacuum build-up: From 3 to 4 min

-

Suction achievement of the probe with Ø 5 mm: From 1.0 to 1.5 l / min.

-

Suction achievement of the probe Ø 6 mm: From 2.0 to 2.5 l / min.

-

Suction achievement of the probe with Ø 8 mm: From 3.5 to 4.0 l / min., min. oil temperature: 70 °C

-

Spraying: Container, RAL 7040, window-grey semi-gloss / rallying funnel to Pantone 294c, blue semi-gloss

-

A vacuum is built-up by the Venturiblock and air pressure in the tank

Moreover:

-

with manometre / vacuum-metre for the indication of pressure and low-pressure

-

suction via dipstick opening

-

with level indicator

-

the security overpressure valve is firmly put on 0.5 bar, with throttle valve

-

with insertion nipple for Rectus coupling type 26, NW 7.2 mm 20 062, ball cock

-

with suction tube (2 m), with coil spring; suction probes Ø 5 / 6 / 8 mm; with adaptor for BMW, Mercedes, VW, Audi

-

with probe holder

-

with clear tube (2 m) with metal - exhaust manifold and ball cock

-

Rallying funnel with removable sieve and additional coarse sieve

-

The devices are subject to the regulations for pressure tank of the test group 1

The Starterkit in 2009 can be equipped with the following options:

-

Petrol/ diesel drilling device STH-TBR in 2010/001

-

Shock absorber drilling device STB / RA / in 2010/003

For further information please use our [contact form](#) or contact us under phone: **+ 49 (0) 9401 605662**